



HUG THE TERRAIN. Even when facing varied terrain and unfavorable ground conditions, the RTX250's high-mount track design offers outstanding traction and minimizes ground disturbance.



MINIMIZE SERVICE TIME AND TOOLS. You know serviceability isn't an option. The engine cover design offers virtually "no-tool" access to all daily and weekly service points, making for quick service turnaround.



SLENDER PROFILE DESIGN. A 34.5" (87.6 cm) width helps the unit fit through tight areas and narrow gates.



**OPERATORS, START YOUR ENGINE.** The 25 hp (19 kW) Kohler electronic fuel-injected (EFI) gasoline engine offers improved fuel economy reducing greenhouse gas by an average of 25 percent — as compared to conventional carbureted engines. And, best of all, makes choke cables obsolete. Simply put, it's time to start your trencher like you would your car.



**OUTBOARD BEARING SUPPORT:** This feature provides protection for the headshaft when trenching in difficult conditions, helping to lower the overall cost of operation.



VZ STEERING. Instead of additional levers and steerable wheels, the operator can turn the machine using only the handlebars. These bars also provide additional leverage when operating in difficult terrain.















# **RTX250** PEDESTRIAN TRENCHER

#### **GENERAL**

Length: 79" (200.1 cm)
Width: 34.5" (87.6 cm)
Height: 48" (121.9 cm)
Weight: 1550 lb (703 kg)

# **TRENCHER**

Digging depth: 48" (121.9 cm) Cutting width: 8" (20.3 cm) Auger diameter: 18" (45.7 cm)

# **ENGINE**

Make/Model: Kohler Command PRO ECH740

Gross horsepower: 25 hp (19 kW) Displacement: 45 cu-in (0.747 L)

Fuel type: Gas

Fuel tank capacity: 6.8 gal (25.7L) Cooling medium: Forced air Max engine operating angle\*: 25°

\*Engine operating angles do not indicate safe machine operating angles.

#### **HYDRAULIC SYSTEM**

Hydraulic tank capacity: 8 gal (30.3 L)

Hydraulic system capacity: 8.5 gal (32.2 L)

Attachment pump relief pressure: 2975 psi (205.1 bar) Ground drive pump relief pressure: 2900 psi (200 bar)

Attachment pump gpm at max engine rpm: 16.1 gpm (60.9 L/min)

## **GROUND DRIVE**

Ground drive type: Hydrostatic

Max forward transport speed: 3.5 mph (5.6 km/h)
Max reverse transport speed: 2.5 mph (4 km/h)

### **OPTIONS**

Backfill blade

Porta Bore

Trencher cleaner

**Extended warranty** 

Special paint

Planned maintenance

Vermeer Confidence Plus® asset protection program

NOTES:	

Vermeer

EQUIPPED TO

DO MORE:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications.

Vermeer, the Vermeer logo, Equipped to Do More and Vermeer Confidence Plus are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kohler is a trademark of Kohler Co.

© 2016 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.