

SC60TX TIER 4i (STAGE IIIB) STUMP CUTTER



EXTENDED WARRANTY. The 3-year/3000-hour extended limited warranty on gearboxes and drivelines offers you peace of mind, in addition to the 1-year/1000-hour Vermeer equipment limited warranty.



POWERFUL PERFORMANCE. With its 60 hp (45 kW) diesel liquid-cooled engine, the SC60tx packs the power needed for bold performance.



YELLOW JACKET™ CUTTER SYSTEM. The Vermeer-exclusive Yellow Jacket cutter system is designed to provide faster, easier serviceability, as well as extended pocket and tooth life.



OPTIONAL REMOTE CONTROL. An optional remote control allows operators to maneuver the stump cutter up to 100' (.5 m) away from the unit. The joysticks and neckstrap help to increase operator control and comfort.



ZERO TURNING RADIUS. The planetary traction drive helps provide increased traction while the counter rotating tracks provide tight maneuvering in difficult jobsite conditions.



VERMEER.COM



**EQUIPPED TO
DO MORE.™**

SC60TX TIER 4i (STAGE IIIB) STUMP CUTTER

GENERAL

Length: 11.8' (3.6 m)

Width: 35" (88.9 cm) narrow mode, 51" (129.54 cm) wide mode

Height: 72" (182.9 cm)

Weight: 3500 lb (1587.6 kg)

ENGINE

Make and model: CAT C2.2T turbocharged Tier 4i (Stage IIIB)

Horsepower: 60 hp (45 kW)

Type of fuel: Diesel

Fuel tank: 12 gal (45.4 L)

HYDRAULIC SYSTEM

Oil-tank capacity: 4 gal (15.1 L)

Oil type: Vermeer HyPower 68

CUTTER WHEEL

Wheel diameter: 23" (58.4 cm) without teeth

Wheel thickness: 1.125" (2.9 cm)

Tooth style: Yellow Jacket cutter system

Number of teeth: 30

Drive: Patented Vermeer gearbox direct-drive system

CUTTING DIMENSIONS

Above ground level: 27" (68.6 cm)

Below ground level: 16" (40.6 cm)

Straight line: 65" (165.1 cm)

Chip containment: 23 cu ft (.7 cu m)

GROUND DRIVE

Track type: Rubberized, steel-reinforced

Track width: 9" (22.9 cm)

Ground pressure (soft ground): 4.1 psi (28.3 kPa)

Ground pressure (hard surface): 12.6 psi (86.9 kPa)

Drive type: Integral motor and planetary unit

High-range travel speed: 110 fpm (33.5 m/min)

Low-range travel speed: 64 fpm (19.6 m/min)

Brakes: Spring-applied, hydraulically released

NOTES:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More. and Yellow Jacket are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. © 2013 Vermeer Corporation. All rights reserved. Printed in the U.S.A. Please recycle.

