


T555III TRENCHER



SMARTTEC ELECTRONIC CONTROL SYSTEM. SmartTEC performance software helps optimize productivity with real-time machine control prompts. Monitor and record functions encourage proactive machine maintenance and operator performance analysis. Available on all Vermeer TEC® Plus system-equipped machines.



OPTIONAL AUTO TILT TRACK. An oscillating track frame allows the track to follow the ground's contour, providing a vertical trench on slopes up to 10 degrees.



HYDROSTATIC ROCKWHEEL ATTACHMENT. Powered by a hydrostatic motor, the rockwheel attachment has the ability to cut a trench up to 36" (91.4 cm) in depth and 6" (15.2 cm) in width.



VANTAGE TRACK. Relax in the confidence that your investment is protected and your entire closed-loop hydrostatic system is covered with an optional 3-year/3000-hour Extended Care Service program.



ENHANCED COOLING SYSTEM. Improvements to the cooling system on the T555III Commander® 3 trencher have resulted in a 5 percent increase in available horsepower to the ditch.



FULL-FUNCTION REMOTE CONTROL. The T555III is available with a wireless remote control that can provide full operator function remotely.

T555III TRENCHER

GENERAL DIMENSIONS

Approach angle: 17°

Height: 9.8' (3 m)

Length range: 21' – 25' (6.4 m – 7.6 m)

Weight range (tractor plus trencher attachment): 28,000 lb - 36,000 lb (12,700.6 kg - 16,329.3 kg)

Width range: 8.1' – 8.5' (2.5 m – 2.6 m)

ENGINE OPTION ONE

Make and model: John Deere 6068H

Gross horsepower: 185 hp (138 kW)

Engine rpm: 2400

Fuel consumption @ full load: 9.3 gph (35.2 L/hr)

EPA Certification Family: Tier 3

ENGINE OPTION TWO

Make and model: John Deere 6068H

Gross horsepower: 185 hp (138 kW)

Engine rpm: 2400

Fuel consumption @ full load: 9.3 gph (35.2 L/hr)

EPA Certification Family: Tier 4 Final (Stage IV)

TRACKS

Ground pressure: 5.4 psi – 8.4 psi (37.2 kPa – 57.9 kPa)

Tilt track with Auto Level available: Yes, max angle 10°

Track length: 8.8' (2.7 m)

Track pad type: Single, triple or rubber grouser

Track pad width range: 15" - 24" (38.1 cm - 61 cm)

Track size: FL6

Travel speed max: 203 fpm (61.9 m/min)

Service brakes: Hydrostatic

CONVEYOR

Belt width: 24" (61 cm)

Max conveyor belt speed: 823 fpm (250.9 m/min)

Conveyor belt style: Cleated

Conveyor length: 7.8' or 11.7' (2.4 m or 3.6 m)

Conveyor shift available: Yes

Conveyor shift distance: 27" (68.6 cm)

Conveyor style: Flat

Discharge direction: Right or left

Discharge height: 43.5" or 45.5" (110.5 cm or 115.6 cm)

CAB

Air conditioner/heater: Yes, with cab option only

Air suspension seat: No

AM/FM stereo with weather band: Yes, with cab option only

Elevating: No

Pressurized/Filtered air: Yes

ROPS: Standard

TRENCHER ATTACHMENT

Boom depth options: 4', 5', 6' or 8' (1.2 m, 1.5 m, 1.8 m or 2.4 m)

Boom top rollers: Yes; on 40" (101.6 cm) end idler only

Chain speed range: 429 fpm – 730 fpm (130.8 m/min – 222.5 m/min)

Cutting width range: 6" – 24" (15.2 cm – 61 cm)

End idler diameter: 20" or 40" (50.8 cm or 101.6 cm)

ROCKWHEEL ATTACHMENT

Weight (tractor plus attachment): 36,500 lb (13,623.3 kg)

Max cutting depth: 36" (91.4 cm)

Cutting width: 4.8" and 6" (12.1 cm and 15.2 cm)

Cutter tip speed (low range): 1112 fpm (338.9 m/min)

Cutter tip speed (high range): 2225 fpm (678.2 m/min)

OPTIONS

Rockwheel

Loadout conveyor

Reel carrier

Tile box

Remote control

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Commander and TEC are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. John Deere is a trademark of Deere and Company. © 2016 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

