

# T955III TRENCHER



**TEC® PLUS ELECTRONIC CONTROL SYSTEM.** The operating system communicates with multiple control modules located throughout the machine for real-time performance data and advanced troubleshooting capabilities.



**ROTARY POWER TRENCHER DRIVE MOTOR.** A rotary power trencher drive motor and splined headshaft produce a lower speed and higher torque which provide superior ground penetration and low chain wear for better production results.



**ELEVATING ROPM CAB.** The elevating rollover protective module cab features LEXAN® glass, filtered and pressurized air, heating and air-conditioning. The cab's vantage point allows a virtually unrestricted view of the boom, trench and conveyor.



**VANTAGE TRACK.** Relax in the confidence that your investment is protected and your entire closed loop hydrostatic system is covered with either a 3-year/3000-hour or 5-year/5000-hour Extended Care Service program.



**TERRAIN LEVELER® SURFACE EXCAVATION MACHINE ATTACHMENT.** The T955III has a chain drive Terrain Leveler option for large rock excavation applications including surface mining, overburden removal, site preparation and road demolition.



**FULL FUNCTION REMOTE CONTROL.** The T955III is available with a wireless remote control that can provide full operator function remotely.

# T955III TRENCHER

## GENERAL DIMENSIONS

Approach angle: 16°

Height: 11.1' (3.4 m)

Length range: 32.2' – 39.7' (9.8 m – 12.1 m)

Weight range (tractor plus trencher attachment): 96,000 lb – 109,000 lb (43,544.9 kg – 49,441.6 kg)

Width: 9.5' (2.9 m)

## ENGINE

Make and model: Caterpillar C13 ACERT

Gross horsepower: 415 hp (310 kW)

Engine rpm: 2100

Fuel consumption @ full load: 20.9 gph (79.1 L/hr)

## TRACKS

Ground pressure: 11.7 psi – 13.3 psi (80.7 kPa – 91.7 kPa)

Tilt track with Auto Level available: No

Track length: 13.4' (4.1 m)

Track pad type: Single, double or triple grouser

Track pad width: 24" (61 cm)

Track size: D6

Travel speed max: 148 fpm (45.1 m/min)

Service brakes: Hydrostatic

## CONVEYOR

Belt width: 30" (76.2 cm)

Max conveyor belt speed: 1070 fpm (326.1 m/min)

Conveyor belt style: Cleated or finger-type

Conveyor length: 9' or 14' (2.7 m or 4.3 m)

Conveyor shift available: Yes

Conveyor shift distance: 15" or 65" (38 cm or 165.1 cm)

Conveyor style: Curved

Discharge direction: Right or left

Discharge height: 62" or 76" (157.5 cm or 193 cm)

## CAB

Air conditioner/heater: Yes

Air suspension seat: No

AM/FM stereo with weather band: Yes

Elevating: Yes

Pressurized/Filtered air: Yes

Rollover protective module (ROPM): Yes

Level II FOPS: Yes

## TRENCHER ATTACHMENT

Boom depth options: 6', 8', 10' or 12' (1.8 m, 2.4 m, 3 m or 3.7 m)

Boom top rollers: Yes

Chain speed range: 316 fpm – 643 fpm (96.3 m/min – 196 m/min)

Cutting width range: 18" – 42" (45.7 cm – 106.7 cm)

End idler diameter: 40" (101.6 cm)

## CHAIN DRIVE TERRAIN LEVELER ATTACHMENT

Weight (tractor plus attachment): 118,000 lb (53,523.9 kg)

Max cutting depth: 32" (81.3 cm)

Cutting width: 132" (335.3 cm)

Drum tilt available: No

Max drum speed rpm: 59

Laser and GPS acceptable: Yes

Digging chain size: 4501

## OPTIONS

Loadout conveyor

Terrain Leveler attachment

Remote control