RTX200
PEDESTRIAN TRENCHER

ENHANCED VZ STEERING. Operators can steer the machine using only the handlebars — rather than traditional methods using levers or steering wheels. These bars also provide additional leverage when operating on difficult terrain.

DEPTH-CONTROL. Elimination of the tail wheel on the track unit provides trenching depth-control in uneven ground conditions and convenience to move through tight spaces.

HIGH-TORQUE DIGGING. The RTX200 is equipped with a 20.5 hp (15 kW) Kohler engine for optimal power on your jobsite.

SLENDER PROFILE. The 35" (88.9 cm) width allows the RTX200 to access compact spaces — including passing through typical backyard gates.

EASE OF MAINTENANCE. The hydraulic hoses and hard-line design provide convenient service and maintenance.

MASTER YOUR TERRAIN. Option of tracks or tires helps you attain maximum performance and productivity despite varying surface conditions.

VERMEER-WANT.COM.AU

Vermeer
EQUIPPED TO DO MORE.

RTX200 PEDESTRIAN TRENCHER

GENERAL WEIGHTS AND DIMENSIONS

Weight (basic tractor with tracks): 1170 lb (530.7 kg)
Weight (basic tractor with tires): 940 lb (426.4 kg)
Length (basic tractor with tracks): 73" (185.4 cm)
Length (basic tractor with tires): 83" (210.8 cm)
Width: 35" (88.9 cm)
Height: 46" (116.8 cm)
Wheel base: 33.2" (84.3 cm)
Tread width: 8.5" (21.6 cm)

TRENCHER

Digging depth: 36" (91.4 cm)
Cutting width: 4" – 6" (10.2 cm – 15.2 cm)
Auger diameter: 16" (40.6 cm)
Min transport length: 89" (226 cm)

ENGINE

Make/Model: Kohler CH640
Gross horsepower: 20.5 hp (15 kW)
Displacement: 41.1 cu-in (.67 L)
Fuel type: Gasoline
Fuel tank capacity: 1.6 gal (6.1 L)
Cooling medium: Forced air
Max operating angle (fore/aft)*: 25°
Max operating angle (left/right)*: 25°
Number of cylinders: 2
Aspiration: Natural
Engine oil capacity: .5 gal (1.9 L)

*Engine operating angles do not indicate safe machine operating angles.

HYDRAULIC SYSTEM

Hydraulic tank capacity: 10.75 gal (40.7 L)
Hydraulic system capacity: 11.25 gal (42.6 L)
Attachment pump flow at max engine rpm: 10.3 gpm (39.0 L/min)
Ground drive flow at max engine rpm: 5.4 gpm (20.4 L/min)

GROUND DRIVE

Ground drive type: Hydrostatic
Max forward transport speed at full throttle: 3.1 mph (5.0 km/h)
Max reverse transport speed at full throttle: 1 mph (1.6 km/h)

OPTIONS

Backfill blade
Trench cleaner
Extended warranty
Special paint
Planned maintenance
Vermeer Confidence Plus® asset protection program

NOTES:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.
Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications.
Vermeer, the Vermeer logo and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kohler is a trademark of Kohler Co.
© 2016 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

Vermeer
EQUIPPED TO DO MORE.